

VTO2000A-X Series

# VTO2000A-X Series

## Module Outdoor Station



### Features

- HD CMOS camera
- Stainless steel panel, IP54,IK07
- Night vision & Voice indication
- Video & Audio messaging
- Modular design( Max 9 modules, VTO2000A-C needed)
- Surface mounted & Flush mounted



### Technical Specification

Mode	VTO2000A-C
<b>System</b>	
Main Processor	Embedded Micro Processor
Operation System	Embedded LINUX OS
<b>Video</b>	
Video Compression	H.264
Image Sensor	1/3" 1.3MP CMOS
Lens	2.8mm
Angle of View	D:117° H:87° V:63°
Day/Night	Color Image
<b>Audio</b>	
Audio Compression	G.711
Audio Input	Omnidirectional Mic
Audio Output	Built-in Speaker
Bidirectional Talk	Support Dual-way Bidirectional talk
<b>Operation Mode</b>	
Keypad	Mechanical Button
<b>Interface</b>	
Door Control	2(1 relay out for main lock, 1 extended by access control module)
Alarm In	2(1ch unlock button, 1ch feedback)
RS485	1
<b>Network</b>	
Ethernet	10M/100Mbps Self-adaptive
Network Protocol	TCP/IP

### General

Ingress Protection	IP54, IK07
Tamper Switch	1
Installation	Surface & Flush
Material	Stainless Steel
Power	DC 12V
Power Consumption	Work ≤10W
Working Temperature	-30°C to +60°C
Relative Humidity	10%RH-90%RH
Dimensions	110.7mm×118.1mm×42.3mm
Weight	0.36kg

Model	VTO2000A-B/B1/B5	VTO2000A-R
Body Approaching	-	Support, 0.6m

### General

Material	Stainless Steel	
Power	Supply by VTO2000A-C	
Power Consumption	Standby ≤0.1W, Work ≤0.45W	Standby ≤0.3W, Work ≤0.3W
Working Temperature	-30°C to +60°C	
Relative Humidity	10%RH-90%RH	
Dimensions	110mm×120mm×24.9mm	
Weight	0.27Kg	

# VTO2000A-X Series

Model	VTO2000A-K
Proximity Sensor	-

## General


Material	Stainless Steel
Power	Supply by VTO2000A-C
Power Consumption	Standby $\leq 0.1W$ , Work $\leq 0.45W$
Working Temperature	-30°C to +60°C
Relative Humidity	10%RH–90%RH
Dimensions	110mm×120mm×29.0mm
Weight	0.32kg

Model	VTO2000A-F	VTO2000A-E
Proximity Sensor	-	-


## General

Material	Stainless Steel	
Power	Supply by VTO2000A-C	-
Power Consumption	Standby $\leq 0.1W$ , Work $\leq 0.45W$	-
Working Temperature	-30°C to +60°C	-20°C to +60°C
Relative Humidity	10%RH–90%RH	
Dimensions	110mm×120mm×24.9mm	
Weight	0.27kg	


## Dimensions



VTO2000A-C front panel and rear panel




VTO2000A-B1 VTO2000A-B VTO2000A-B5 VTO2000A-E



VTO2000A-R VTO2000A-K VTO2000A-F Rear panel

## View Area



## Application

