

DS-PS1-I-WB Wireless Internal Sounder

The wireless internal sounder, supporting 433 MHz wireless communication, Tri-X wireless protocol, multiple enrollment methods, two-way wireless communication, multiple alarm sounds, and strobe light indication, is used for instant alarm alerting.

Key Features

- 433 MHz two-way wireless communication
- Configurable arming/disarming prompt sound and LED indicator
- 3 years battery life span (triggered every two weeks and alerting 90 s for each triggering)
- AES-128 encryption
- Front and rear panel tamper-proof
- 3 kinds of alarm sounds: fire alarm, panic alarm, and intrusion alarm
- Buzzer Decibel: 90 to 110 dB
- Fully remote configurable through App
- Multiple enrollment methods and easy installation design
- Frequency hopping against jamming for reliable transmission

Available Model

- DS-PS1-I-WB (433MHz)



Model		DS-PS1-I-WB
RF	Frequency	433 MHz
	Modulation	2GFSK
	Method	Two-way communication
	RF encryption	AES-128
	RF distance	900m (open area)
Electrical & battery	Power	Battery
	Consumption	Static consumption: 30 to 40uA
	Battery life span	3 CR123A, 3 years in work status (triggered every two weeks and alerting 90 s for each triggering)
Interface and component	Power switch	Supported
	Tamper switch	Supported, Front and rear tamper-proof
	Indicator	Indicator: Red/Green/Amber Strobe light: Red/Blue
	Buzzer	Decibel: 90 to 110 dB
General	Operation temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Operation humidity	10% to 90% (no condensing)
	Color	White
	Material	PC+ABS
	Dimension (W × H × D)	88× 88 × 32 mm (3.46" ×3.46" × 1.26")
	Weight	169.5 g (6.0 oz)
	Installation	Wall mounting
Approvals	FCC	Supported
	CE/CB	Supported
	RCM	Supported
	Rohs/Reach/WEEE	Supported

Distributed by



www.vigilanciainteligente.com

Tel: San Borja 924 616170 / 945 509622
La Molina 01 6409957 / 950 412169

HIKVISION®**Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
sateru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com